

OBMIAR

Lp.	Podstawa	Opis i wyliczenia	j.m.	Poszcz.	Razem
1	KNR 4-01 0713-01 116 116 116a 116a 112 112 200 200	Przecieranie istniejących tynków wewnętrznych z zeszkobaniem farby lub zdzieraniem tapet na ścianach 5.77*5.85 (5.77+5.85)*2*3.15-2.42*2.15*2 5.77*2.82 (5.77+2.82+2.82)*3.15-2.42*2.15 3.00*3.00 (3.00+3.00)*2*3.17 5.77*2.82 (3.00+3.00)*2*3.17	m ² m ² m ² m ² m ² m ² m ² m ² m ²	 33.755 62.800 16.271 30.739 9.000 38.040 16.271 38.040	
				RAZEM	244.916
2	NNRNKB 202 1134-01 116 116 116a 116a 112 112 200 200	Gruntowanie podłoża preparatami "CERESIT CT 17" i "ATLAS UNI GRUNT" - po- wierzchnie poziome 5.77*5.85 (5.77+5.85)*2*3.15-2.42*2.15*2 5.77*2.82 (5.77+2.82+2.82)*3.15-2.42*2.15 3.00*3.00 (3.00+3.00)*2*3.17 5.77*2.82 (3.00+3.00)*2*3.17	m ² m ² m ² m ² m ² m ² m ² m ² m ²	 33.755 62.800 16.271 30.739 9.000 38.040 16.271 38.040	
				RAZEM	244.916
3	KNR 9-24 0208-02 116,116a, 200,112	Montaż narożników ochronnych mocowanych w narożach prostych - analogia 2.15*6+2.47*6+2.00*3	m m	 33.720	
				RAZEM	33.720
4	KNNR 2 0802-06 116 116 116a 116a 112 112 200 200	Gładzie gipsowe jednowarstwowe na ścianach i sufitach 5.77*5.85 (5.77+5.85)*2*3.15-2.42*2.15*2 5.77*2.82 (5.77+2.82+2.82)*3.15-2.42*2.15 3.00*3.00 (3.00+3.00)*2*3.17 5.77*2.82 (3.00+3.00)*2*3.17	m ² m ² m ² m ² m ² m ² m ² m ² m ²	 33.755 62.800 16.271 30.739 9.000 38.040 16.271 38.040	
				RAZEM	244.916
5	KNR 2-02 2009-07 116 116 116a 116a 112 112 200 200	Tynki (gładzie) jednowarstwowe wewnętrzne gr. 3 mm z gipsu szpachlowego wy- konywane ręcznie na ścianach - dodatek za pogrubienie o 2 mm 5.77*5.85 (5.77+5.85)*2*3.15-2.42*2.15*2 5.77*2.82 (5.77+2.82+2.82)*3.15-2.42*2.15 3.00*3.00 (3.00+3.00)*2*3.17 5.77*2.82 (3.00+3.00)*2*3.17	m ² m ² m ² m ² m ² m ² m ² m ² m ²	 33.755 62.800 16.271 30.739 9.000 38.040 16.271 38.040	
				RAZEM	244.916
6	KNR 2-02 1505-03 116 116a 112 200	Dwukrotne malowanie farbami emulsyjnymi sufitów 5.77*5.85 5.77*2.82 3.00*3.00 5.77*2.82	m ² m ² m ² m ²	 33.755 16.271 9.000 16.271	
				RAZEM	75.297
7	KNR 2-02 1505-03+ KNR2- 021505-04 116 116a 112 200	Gruntowanie i dwukrotne malowanie tynków ścian farbą lateksową półmat odporną na szorowanie (5.77+5.85)*2*3.15-2.42*2.15*2 (5.77+2.82+2.82)*3.15-2.42*2.15 (3.00+3.00)*2*3.17 (3.00+3.00)*2*3.17	m ² m ² m ² m ²	 62.800 30.739 38.040 38.040	
				RAZEM	169.619
8	KNR 4-01 1212-19 116 116a 112 200	Dwukrotne malowanie farbą olejną grzejników radiatorowych 0.60*0.20*2*26 0.60*0.20*2*15 0.60*0.20*2*10 0.60*0.20*2*15	m ² m ² m ² m ²	 6.240 3.600 2.400 3.600	
				RAZEM	15.840
9	KNNR-W 3 0801-07 116 116a	Zerwanie posadzek z tworzyw sztucznych 5.77*5.85 5.77*2.82	m ² m ² m ²	 33.755 16.271	